

KT Serisi / KT Series / KT Serie

Tablo / Table / Tabelle 1 Fc

Acık Kompresör Open Compressor Offener Kompressor	Tc	Te (Evaporasyon sıcaklığı / Evaporation temperature / Verdampfungstemperatur °C										
	°C	-40	-35	-30	-25	-20	-15	-10	-5	0	5	10
	35	1,45	1,40	1,36	1,32	1,27	1,24	1,21	1,18	1,15	1,12	1,10
40	1,50	1,45	1,40	1,35	1,31	1,28	1,24	1,21	1,18	1,15	1,12	
45	1,55	1,48	1,43	1,38	1,34	1,31	1,27	1,25	1,22	1,18	1,16	
50	1,65	1,53	1,47	1,42	1,38	1,34	1,31	1,28	1,25	1,22	1,19	
55	1,68	1,62	1,55	1,50	1,44	1,39	1,35	1,31	1,28	1,24	1,22	

Tablo / Table / Tabelle 2 Fc

Hermetik yarı hermetik komp Hermetic, semi hermetic comp Hermetischer, halbhermetischer	Tc	Te (Evaporasyon sıcaklığı / Evaporation temperature / Verdampfungstemperatur °C										
	°C	-40	-35	-30	-25	-20	-15	-10	-5	0	5	10
	35	1,87	1,73	1,63	1,55	1,50	1,44	1,39	1,35	1,31	1,26	1,22
40	1,95	1,81	1,70	1,62	1,55	1,49	1,44	1,39	1,35	1,30	1,25	
45	2,05	1,90	1,78	1,68	1,61	1,54	1,49	1,44	1,39	1,35	1,30	
50	2,15	2,00	1,85	1,75	1,67	1,60	1,54	1,48	1,44	1,39	1,35	
55	2,28	2,10	2,00	1,85	1,73	1,66	1,60	1,54	1,48	1,44	1,39	

Tablo / Table / Tabelle 3 Fy

M	0	200	400	600	800	1000	1200	1400
Fy	1	1,013	1,027	1,042	1,058	1,074	1,090	1,107
M	1600	1800	2000	2200	2400	2600	2800	3000
Fy	1,124	1,142	1,160	1,180	1,201	1,222	1,243	1,265

Tablo / Table / Tabelle 4 Fr

R	R22	R134a	R404A
Fr	1,04	1,07	1

Tablo / Table / Tabelle 5 Fa

Ta(°C)	5	10	15	20	25	30	35	40	45	50
Fa	0,92	0,93	0,94	0,95	0,97	0,98	1	1,02	1,03	1,05

Tablo / Table / Tabelle 6 Fm

Fin Malzemesi Fin Material Lamellenmaterial	Alüminyum Folyo Aluminium Fin Aluminium	Kaplamalı Alüminyum Coated Aluminium Beschichtetes Aluminium	Bakır Folyo Copper Fin Kupfer Folie
Faktör / Factor / Faktor	1	0,97	1,03